



Technical Data Sheet

SINTMARE 2T

2T lubricant for outboard engines

"Ashless" lubricant for water-cooled two-stroke outboard engines; it responds to NMMA TC-W3 specification, thus guaranteeing exceptional protection and lubrication of any model at any percentage of mixing foreseen by the manufacturers. Can be used both for the manual preparation of petrol-oil mixtures and in separate lubrication systems.

Applications & Benefits

- **Mixing properties**

It has an excellent self-mixing capacity according to the requirements of the current systems, ensuring the immediate formation of a homogeneous mixture in any thermal condition.

- **Protection**

Ensures perfect lubrication and therefore protection of all moving parts, even when low concentrations are used as required by manufacturers.

- **Low Smoke**

The formulation is designed not to give rise to ash formations and thus avoid the presence of deposits on the surfaces of the combustion chamber and the annoying smoke phenomena.

Specifications & Approvals

- **Approvals:**

NMMA TC-W3

*For further information please contact the Technical Service.

Chemical-Physical Characteristics

Test	Method	Sintmare 2T
Density @ 15°C, kg/dm ³	ASTM D 4052	0.865
Viscosity cSt @ 40°C cSt @ 100°C	ASTM D 445	35.0 6.0
Viscosity Index - Unit	ASTM D 2270	130
Flash point, °C	ASTM D 92	225
Pour point, °C	ASTM D 97	-27

NOTE: The above values are "typical" for normal production tolerance and do NOT constitute a specification.

Storage, Health & Environment

- Storage & Health

It is recommended to store the covered SINTMARE 2T lubricant. If, by necessity, the storage is carried out outdoors, it is recommended to place the stems, possibly under a roof, in a horizontal position and if kept in a vertical position cover them with a lid to avoid water infiltration. It is advisable not to store the packages at temperatures above 60°C or directly in the sun as it is good to keep them in places not subject to frost.

SINTMARE 2T does not present health effects when used correctly, applying normal personal hygiene standards.

- Environment

Do not discharge new and/or used lubricant into the sewage system, soil or watercourses. The used lubricant must be delivered to an authorized collection point.

Additional information

- Safety Data Sheet

It is supplied separately and must be considered for the relative information or can be easily downloaded from the website www.rilub.it

For further information contact the technical service:



+390813383413



infolab@rilub.it