



## Technical Data Sheet

# *EULOGORI*

## *Mineral multigrade lubricant for vintage engines*

Provides reliable protection for older engines that have high mileage, helping to prevent the formation of sludge and reducing wear phenomena. The improved formula allows its use where required specifications API SJ/CF.

### Applications & Benefits

#### - **Cleaness Technology**

It guarantees a better degree of cleaning than conventional mineral-based lubricants. It protects against the formation of lacquers and bumps that are extremely damaging to the engine.

#### - **Wear Protection**

The additives create a thin film between the moving mechanical components protecting them from wear and tear.

#### - **Viscosity**

High viscosity reduces leakage even in engines with high mileage, reducing lubricant consumption.

#### - **One-Technology**

The additives used allow the lubricant to be used in petrol, diesel and gas engines.

#### - **Additional Grade**

On some occasions, the classic gradation SAE 20W-50 may be insufficient against the drawing phenomena; The SAE 20W-60 gradation (green color) can be used for this purpose.

### Specifications & Approvals

#### - **Exceeds the specifications listed below:**

SAE 20W-50 & SAE 20W-60

API SJ/CF

\*For further information please contact the Technical Service.

## Chemical-Physical Characteristics

Test	Method	Eulogori	
		20W-50	20W-60
<b>Gradazione SAE</b>	-	<b>20W-50</b>	<b>20W-60</b>
Color	Visual	Amber	Green
Density @ 15°C, kg/dm <sup>3</sup>	ASTM D 4052	0.880	0.885
Viscosity cSt @ 40°C cSt @ 100°C	ASTM D 445	150.0 19.0	190.0 24.0
Viscosity Index - Unit	ASTM D 2270	130	130
Flash point, °C	ASTM D 92	245	250
Pour point, °C	ASTM D 97	-30	-27

NOTE: The above values are "typical" for normal production tolerance and do NOT constitute a specification.

## Storage, Health & Environment

### - Storage & Health

It is recommended storing the EULOGORI lubricant under cover. If storage is carried out outdoors, it is recommended to position the drums, preferably under a roof, in a horizontal position and, if kept upright, cover them with a lid to prevent water infiltration. It is advisable not to store the packs at temperatures above 60°C or directly to the sun as it is good to keep them in places not subject to freezing.

EULOGORI has no health effects when properly used, applying the standard personal hygiene standards.

### - Environment

Do not discharge the new and/or exhausted lubricant into the sewage system, soil or watercourses. Exhausted lubricant must be delivered to an authorized collection point.

## Additional information

### - Safety Data Sheet

It is provided aside and must be considered for its information or can be easily downloaded from [www.rilub.it](http://www.rilub.it)

Contact your technical service for more information:



+390813383413



[infolab@rilub.it](mailto:infolab@rilub.it)